





Centerless grinding machines - RSC 350

The Magnaghi centerless grinding machines are sturdy and very compact units.

Grinding machines are available in 3 different versions:

- MANUAL VERSION
- AUTOMATIC CYCLE VERSION
- AUTOMATIC DRESSING CYCLE VERSION Operation with infeed (plunge) or thru-feed manual or automatic cycle.

Available in 2 versions: Electromechanical or CNC. With possibility of machining cylindrical parts with diameters between 1 and 50 max length 120 mm with infeed (plunge) operation.



Centerless Grinding machines features		RSC 350
Minimum grinding diameter	mm	2
Maximum grinding diameter for components up to 150mm. 6" long	mm	85
Maximum diameter for pieces of tube to 200 mm. 7,7/8 " long	mm	100
Grinding wheel (dia./width/hole)	mm	350x120x200
Control wheel (dia./width/hole)	mm	250x120x150
Grinding wheel speed	giri/min.	1800
control wheel speed with control lever in position 1	rpm/min.	18
control wheel speed with control lever in position 2	rpm/min.	24
control wheel speed with control lever in position 3	rpm/min.	34
control wheel speed with control lever in position 4	rpm/min.	250
Total power installed	HP	10
Overall dimensions	mm	1760 x 1350 x 1500
Weight of the machine	Kg.	1500

web: www.comasmotek.it e.mail: info@comasmotek.it