



Comasmo Tek

Manual Centerless grinding machines - RSC 350M

The Magnaghi centerless grinding machines in manual version are easy-to-use, compact and flexible units. These grinding machines feature infeed (plunge) or thru-feed operation.

Operation is electro-mechanical only.

Possibility of machining cylindrical parts with diameters between 1 and 50 max length 120 mm. (infeed)

The excellent value for money makes this centerless grinding machine ideal for anyone with medium small and diversified production requirements.



| Manual Centerless Grinding machines features | | RSC 350 |
|---|-----------|--------------------|
| Minimum grinding diameter | mm | 2 |
| Maximum grinding diameter for components up to 150mm. 6" long | mm | 85 |
| Maximum diameter for pieces of tube to 200 mm. 7,7/8 " long | mm | 100 |
| Grinding wheel (dia./width/hole) | mm | 350x120x200 |
| Control wheel (dia./width/hole) | mm | 250x120x150 |
| Grinding wheel speed | giri/min. | 1800 |
| control wheel speed with control lever in position 1 | rpm/min. | 18 |
| control wheel speed with control lever in position 2 | rpm/min. | 24 |
| control wheel speed with control lever in position 3 | rpm/min. | 34 |
| control wheel speed with control lever in position 4 | rpm/min. | 250 |
| Total power installed | HP | 10 |
| Overall dimensions | mm | 1760 x 1350 x 1500 |
| Weight of the machine | Kg. | 1450 |

COMASMO Tek s.r.l.

Sede legale e Commerciale: Via L. Da Vinci 1/3 - 20090 Segrate (MI) - Italia -
tel. (+39) 02 2133141 - Fax: (+39) 02 2135160
Partita Iva e codice fiscale : 06729890969

web: www.comasmotek.it e.mail: info@comasmotek.it